



IMANTS

ShockWave

1.0 / 1.6 / 2.1 / 220 / 275

The Imants ShockWave is the perfect linear decompactor for heavily used areas where play can't stop. This machine is designed to revitalise fine turf and sports fields by relieving soil compaction, improving aeration and removing surface water, all whilst causing minimal surface disruption so play can resume quickly and safely. All ShockWave models feature a no-chains, direct drive design, maintenance free 'sealed for life' bearings and no shear bolts.

Imants ShockWave 220/275 brings linear decompaction to wide areas, making it the perfect machine for contractors. Using thicker 15mm knives and featuring hydraulic depth adjustment from the tractor, this machine takes the ShockWave's attributes of relieving soil compaction, improving aeration and removing surface water and applies them to large turf areas that need to be revitalised and ready for action quickly.

Campey supply market leading, innovative turf care machinery worldwide, we're continually researching new techniques and refining existing practices to help turf care professionals achieve perfection.

Call +44 (0)1260 224568, email info@campeyturfcare.com or visit www.campeyturfcare.com

CampeyTurfCare
 CampeySportsTurfMachinery
 CampeyMachinery
 CampeyTurfCare

- Removes surface water

- Provides maximum decompaction in the rootzone to improve turf quality

- Features a no-chains direct drive, 'sealed for life' bearings and mechanical drive overload protection

- Improves drainage and water percolation

- Minimal surface disruption allows play to continue quickly

Designed to revitalise heavy wear areas by relieving soil compaction, improving aeration and removing surface water.

Specification	1.0	1.6	2.1	220	275
Working width	1.00m	1.60m	2.10m	2.20m	2.75m
Working depth	110mm - 250mm	110mm - 250mm	110mm - 250mm	120mm - 280mm	120mm - 280mm
Number of blades	12	18	24	24	30
Blade thickness	12mm	12mm	12mm	15mm	15mm
Blade spacing	265mm	265mm	265mm	275mm	275mm
Machine length	1.38m	1.38m	1.38m	2.20m	2.75m
Machine width	1.20m	1.75m	2.30m	2.50m	3.00m
Machine weight (approx.)	525kgs	635kg	750kg	1250kg	1750kg
Power requirement	41 - 54hp	41 - 54hp	41 - 54hp	80hp +	100hp +
Tractor requirements	540 pto. Creep gear or hydrostatic drive required				
Operating speed	0.5 - 1.5 mph (0.5 - 2.4kph)				